Gas-Fired Convection

The industrial-duty propane or natural gas convection portable heaters heat quietly and efficiently providing powerful instant heat with no electricity required.

MH-0200-CM10

Frame
✓ *Quick assembly 2-piece burn chamber*
✓ *Durable steel housing*
✓ *Inner windshield protects burner flame from being extinguished*

Heat Output
✓ *Variable heat settings*
✓ *360-degree heat radius for even heating of room*

Components
✓ *Matchless piezo spark ignitor*
✓ *Automatic shut-off if flame is extinguished*

For use in workshops, construction sites, farms and loading docks with proper ventilation.

MODEL NUMBER	MH-0080-CM10	MH-0100-CM1N	MH-0200-CM10
HEAT OUTPUT	60-80,000 BTU	50-100,000 BTU	50-200,000 BTU
HOT-AIR FLOW	N/A	400 CFM	N/A
IGNITION TYPE	Automatic (integral)	Control knob ignition	Push-button
FUEL	Propane	Natural Gas	Propane
FUEL CONSUMPTION	2.3 / 3.7 lb./hr.	2.13 min. / 4.63 max. lb./hr.	3.24 / 9.25 lb./hr.
OPERATING TIME (100 LB. CYL.)	43 / 27 hours	N/A	31 / 11 hours
OPERATING TIME (40 LB. CYL.)	17 / 11 hours	N/A	N/A
OPERATING TIME (20 LB. CYL.)	8 / 5 hours	N/A	N/A
SUGGESTED CYLINDER SIZE	100 lb.	N/A	100 lb.
INLET GAS PRESSURE	N/A	7in. WC minimum / 14in. WC maximum	N/A
HEATING AREA	1,800 sq. ft.	3,000 sq. ft.	4,600 sq. ft.
STAINLESS-STEEL BURNER	No	Yes	No
HOSE & REGULATOR	Yes, 10ft.	No	Yes, 10ft.
DIMENSIONS (LxWxH)	15.7x15.7x21.8in.	15.7x15.7x26.4in.	16x16x26.4in.
SHIP WT.	17 lb.	21 lb.	20 lb.
NET WT.	11.5 lb.	14.3 lb.	14 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.
Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

To see more online, scan here or go to www.mitm.com:

Accessory:

PART NUMBER	DESCRIPTION	FITS MODELS
68-5010	Two cylinder manifold	All models